

High Flexible Shielded Core Type

RoHS

KIFLEX 승인제품

한국산업규격 승인제품

절전기용품 안전인증 승인제품

산업용 공강 차동회기계 케이블

테프론·실리콘 제품

일반제품

참고자료

KIFLEX MPEU - SB

E 150633 AWM 20936 80°C 300V VW-1 AWM I/II A/B 80°C 300V
FT1 KIFLEX MPEU - SB 2C X 24AWG KWANGIL RoHS = M =

Super fine conductor / Colour coded / Braid shielded / Special TPU Sheathed

KIFLEX MPEU - SB is signal interconnecting or control cable used for the cable chains of manufacturing automatic machine or internal wiring of the industrial robots.

Construction

Conductor	Tinned annealed copper standard acc. to IEC 60228 EN 60228, VDE 0295 Class 6
Insulation	Special Polyethylene
Filler	Fabric
Stranding	in layers
Wrapping	Special non-woven Tape
Shield	Tinned copper braid shield
Sheath	Special Polyurethane
Sheath Color	Black(Color can be changed after consultation)

Technical Data

Nominal Rating	80°C, 300V
Insulation Resistance	Min. 1000MΩ/km
Spark Test Voltage	AC 500V
Dielectric Test Voltage	
Core/Core	AC 500V / 1 min
Core/Screen	AC 300V / 1 min
Min. bending radius	
fixed laying	Overall diameter x 10
flexible application	Overall diameter x 12
Temperature range	
fixed laying	-20°C ~ +80°C
flexible application	-10°C ~ +80°C
Toxicity	acc. to RoHS
Fire performance	Flame retardant and self-extinguishing acc. to IEC 60332-1, EN 60332-1 VW-1 acc. to UL 1581 section 1080 FT1 acc. to UL 1581 section 1060

No. of Cores x cross section (No. / mm ²)	Conductor strands (EA / mm)	Conductor diameter (mm)	Insulation diameter (mm)	Overall diameter (mm)	Max. current (A)
2 x 0.2	40/0.08	0.58	1.00	4.6	4.8
3 x 0.2	40/0.08	0.58	1.00	4.7	4.2
4 x 0.2	40/0.08	0.58	1.00	5.1	3.4
6 x 0.2	40/0.08	0.58	1.00	5.7	2.9
8 x 0.2	40/0.08	0.58	1.00	6.4	2.7
10 x 0.2	40/0.08	0.58	1.00	7.0	2.6
12 x 0.2	40/0.08	0.58	1.00	6.9	2.5
15 x 0.2	40/0.08	0.58	1.00	7.4	2.5
20 x 0.2	40/0.08	0.58	1.00	8.2	2.3
2 x 0.3	60/0.08	0.72	1.25	5.2	6.4
3 x 0.3	60/0.08	0.72	1.25	5.4	5.6
4 x 0.3	60/0.08	0.72	1.25	5.7	4.5
6 x 0.3	60/0.08	0.72	1.25	6.5	3.9
8 x 0.3	60/0.08	0.72	1.25	7.4	3.6
10 x 0.3	60/0.08	0.72	1.25	8.2	3.4
12 x 0.3	60/0.08	0.72	1.25	8.1	3.4
15 x 0.3	60/0.08	0.72	1.25	8.7	3.3
20 x 0.3	60/0.08	0.72	1.25	9.7	3.0
2 x 0.5	7/14/0.08	1.04	1.65	6.0	8.0
3 x 0.5	7/14/0.08	1.04	1.65	6.3	7.0
4 x 0.5	7/14/0.08	1.04	1.65	6.8	5.6
6 x 0.5	7/14/0.08	1.04	1.65	7.8	4.9
8 x 0.5	7/14/0.08	1.04	1.65	8.9	4.5
10 x 0.5	7/14/0.08	1.04	1.65	10.2	4.3
12 x 0.5	7/14/0.08	1.04	1.65	10.0	4.2
15 x 0.5	7/14/0.08	1.04	1.65	10.8	4.1
20 x 0.5	7/14/0.08	1.04	1.65	12.2	3.8
2 x 0.75	7/20/0.08	1.24	1.90	6.6	11.2
3 x 0.75	7/20/0.08	1.24	1.90	6.9	9.8
4 x 0.75	7/20/0.08	1.24	1.90	7.5	7.8
6 x 0.75	7/20/0.08	1.24	1.90	8.7	6.9
8 x 0.75	7/20/0.08	1.24	1.90	10.0	6.3
10 x 0.75	7/20/0.08	1.24	1.90	11.4	6.0
2 x 1.25	7/36/0.08	1.66	2.50	7.9	15.2
3 x 1.25	7/36/0.08	1.66	2.50	8.4	13.3
4 x 1.25	7/36/0.08	1.66	2.50	9.0	10.6
6 x 1.25	7/36/0.08	1.66	2.50	10.8	9.3

Other dimensions and colors are possible on request.

Outstanding Features

- Small outer diameter and small bending radius
- Continuously high flexible
- Good EMC characteristics
- Specially formulated durable PE insulation
- No toxicity
- No flame propagation
- Flame retardant and self-extinguishing