



실리콘 고무 튜브(SRT)

Silicon Rubber Tube(SRT)

제품의 설명

- 정격온도 : -50°C ~ 200°C
- 특성 : 높은 열이 발생하는 주변에 슬리브로 사용함.

내경(mm)	내경 공차(mm)	두께(mm)	외경(mm)	시험내 전압(V, 1분간)
1	-0.2, +0.2	0.3	1.6	1500 V
1.5	-0.2, +0.3	0.3	2.1	
2	-0.2, +0.3	0.3	2.6	
2.5	-0.2, +0.3	0.3	3.1	
3	-0.2, +0.3	0.3	3.6	
3.5	-0.2, +0.3	0.3	4.1	
4	-0.2, +0.3	0.3	4.6	
4.5	-0.2, +0.3	0.3	5.1	
5	-0.3, +0.5	0.4	5.8	
5.5	-0.2, +0.3	0.4	6.3	
6	-0.3, +0.5	0.4	6.8	
6.5	-0.2, +0.3	0.4	7.3	
7	-0.3, +0.5	0.4	7.8	
7.5	-0.2, +0.3	0.4	8.3	
8	-0.3, +0.5	0.4	8.8	
9	-0.3, +0.5	0.4	9.8	
10	-0.3, +0.5	0.4	10.8	
11	-0.3, +0.5	0.4	11.8	
12	-0.3, +0.5	0.4	12.8	
13	-0.5, +0.7	0.4	13.8	
15	-0.5, +0.8	0.5	16	
18	-0.5, +0.8	0.5	19	