

# UL Style No. 1333

RoHS



## 테프론(FEP) 절연 전선

Teflon(FEP) insulated wire

### 제품의 설명

- UL File No. E157965
- Standard : UL Subject 758
- Use : Internal wiring of Appliances
- Temperatures exceeding : 150°C

### RATING

STYLE No	Volt.(max)	Tem p.(max)
1333	300V	150°C

도체				절연체		스파크 시험전압 (AC V)	표준조장 (m)
전선규격	단면적 (mm <sup>2</sup> )	구성 (EA / mm)	외경 (mm)	두께 (mm)	외경 ((mm)		
30#	0.06 SQ	7 / 0.102	0.31	0.33	0.97	3,000 V	610
28#	0.09 SQ	7 / 0.127	0.39	0.33	1.05		
26#	0.14 SQ	7 / 0.16	0.49	0.33	1.15		
24#	0.20 SQ	7 / 0.203	0.62	0.33	1.28		
22#	0.30 SQ	13 / 0.18	0.75	0.33	1.41		
20#	0.50 SQ	21 / 0.18	0.95	0.33	1.61		
18#	0.75 SQ	35 / 0.18	1.23	0.33	1.89		
16#	1.25 SQ	55 / 0.18	1.54	0.33	2.20		
14#	2.0 SQ	41 / 0.26	1.92	0.33	2.58		
12#	3.5 SQ	44 / 0.32	2.70	0.33	3.36		
10#	5.5 SQ	68 / 0.32	3.40	0.33	4.06		