

UL Style No. 10109

RoHS



테프론(ETFE) 절연 전선

Teflon(ETFE) insulated wire

제품의 설명

- UL File No. E157965
- Standard : UL Subject 758
- Use : Internal wiring of appliances
- Temperatures exceeding :150°C

RATING

STYLE No	Volt.(max)	Tem p.(max)
10109	300V	150°C

도체				절연체		스파크 시험전압 (AC V)	표준조장 (m)
전선규격	단면적 (mm²)	구성 (EA / mm)	외경 (mm)	두께 (mm)	외경 ((mm)		
32	0.04	7 / 0.08	0.24	0.15	0.54	3,000 V	610
30	0.06	7 / 0.102	0.31	0.15	0.61		
28	0.09	7 / 0.127	0.39	0.15	0.70		
26	0.14	7 / 0.16	0.49	0.15	0.80		
24	0.20	7 / 0.203	0.62	0.15	0.92		
22	0.30	13 / 0.18	0.75	0.15	1.05		
20	0.50	21 / 0.18	0.95	0.15	1.25		
18	0.75	35 / 0.18	1.23	0.15	1.53		
16	1.25	55 / 0.18	1.54	0.20	1.94		
14	2.0	41 / 0.26	1.92	0.20	2.32		
12	3.5	44 / 0.32	2.70	0.25	3.20		
10	5.5	68 / 0.32	3.40	0.25	3.90		
8	8.5	103 / 0.32	4.20	0.64	5.48		
6	14	7 / 13 / 0.45	5.40	0.64	6.68		
4	22	7 / 20 / 0.45	6.70	0.64	7.98		
2	38	19 / 13 / 0.45	9.10	0.89	10.88		
1	50	19 / 17 / 0.45	10.50	0.89	12.28		