

UL Style No. 1331

RoHS



테프론(FEP) 절연 전선

Teflon(FEP) insulated wire

제품의 설명

- UL File No. E157965
- Standard : UL Subject 758
- Use : Internal wiring of Appliances
- Temperatures exceeding : 150°C

RATING

STYLE No	Volt.(max)	Tem p.(max)
1331	600V	150°C

도체				절연체		스파크 시험전압 (AC V)	표준조장 (m)	
전선규격	단면적 (mm ²)	구성 (EA / mm)	외경 (mm)	두께 (mm)	외경 ((mm)			
30#	0.06 SQ	7 / 0.102	0.31	0.51	1.33	6,000 V	610	
28#	0.09 SQ	7 / 0.127	0.39	0.51	1.41			
26#	0.14 SQ	7 / 0.16	0.49	0.51	1.51			
24#	0.20 SQ	7 / 0.203	0.62	0.51	1.64			
22#	0.30 SQ	13 / 0.18	0.75	0.51	1.77			
20#	0.50 SQ	21 / 0.18	0.95	0.51	1.97			
18#	0.75 SQ	35 / 0.18	1.23	0.51	2.25			
16#	1.25 SQ	55 / 0.18	1.54	0.51	2.56			
14#	2.0 SQ	41 / 0.26	1.92	0.51	2.94			
12#	3.5 SQ	44 / 0.32	2.70	0.51	3.72			
10#	5.5 SQ	68 / 0.32	3.40	0.51	4.42			
8#	8 SQ	103 / 0.32	4.20	0.76	5.72			305
6#	14 SQ	7 / 13 / 0.45	5.40	0.76	6.92			
4#	22 SQ	7 / 20 / 0.45	6.70	0.76	8.22			
2#	38 SQ	19 / 13 / 0.45	9.10	0.76	10.62			
1#	55 SQ	19 / 17 / 0.45	10.50	1.14	12.78			